

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(19)

(11) Publication number: **2002001323 A**

Generated Document

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **2000229947**(51) Intl. Cl.: **C02F 1/40**(22) Application date: **22.06.00**

(30) Priority:

(43) Date of application  
publication: **08.01.02**(84) Designated contracting  
states:(71) Applicant: **FUJIWARA MITSUHIRO**(72) Inventor: **FUJIWARA MITSUHIRO**

(74) Representative:

**(54) SCUM WATER  
TREATING APPARATUS**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a scum water treating apparatus which is excellent in separation treatment ability.

**SOLUTION:** This scum water treating apparatus is provided with a separation tank which introduces scum water from a treatment basin such as a circular sedimentation basin or a rectangular sedimentation basin and subjects the scum water to orbital movement, a parting cylinder which leaves a passage for the orbital movement in the separation tank, is erected in such a manner that the upper end exists above the surface of the water and, on the other hand, enables introducing separated water through the lower side, a separated water drawing out cylinder which is disposed in the parting cylinder and enables introducing the separated water into the parting cylinder and a means which draws the separated water from the inside of the separated water drawing out cylinder to the outside. In addition, this scum water

treating apparatus is constituted in such a manner that a scum concentration tank which allows the floating scum to flow in, concentrates the same and enables drawing settled sludge is disposed at the terminal part of the passage which is the inner and outer space between the separation tank and the parting cylinder and the scum after concentration can be discharged.

COPYRIGHT: (C)2002,JPO

